

15" Flex 3 St (8990800)

Polyblend® compound and a sleek design gives you chemical protection and all day comfort



USP Outsole

Power Lug outsole powered by a multi tread design provides exceptional comfort and slip resistance

USP Shaft

Polyblend compound offers superior resistance to fats, oils and chemicals

USP Safety

Steel toe complies with ASTM F2413-11 with steel shank

General

Segment	Food
Material boot shaft	PVC
Material outsole	PVC
Color shaft	Black
Color outsole	Grey
Insole type	Standard insole

Certification

Safety standard USA	ASTM F2413-11 M I/75 C/75 SD
---------------------	------------------------------

Protection & Comfort

Toe cap	Steel
Oil resistant outsole	Yes
Energy absorbing	Yes
Electrical insulation	Antistatic
Fuel oil resistant	Yes

Sizing

Size range US	05-15
---------------	-------

Logistics

Country of origin	United States of America
Intrastat code	64011000

SKU	Size EUR	Size US	Size UK	GTIN	Prs/Outer pack	Outer pack length (mm)	Outer pack width (mm)	Outer pack height (mm)	Prs/Pallet	Pallet height (mm)
8990800.05		05		791079150801	6	542.925	469.9	314.325	132	1880.7875
8990800.06		06		791079150818	6	542.925	469.9	314.325	132	1880.7875
8990800.07		07		791079150825	6	542.925	469.9	314.325	132	1880.7875
8990800.08		08		791079150832	6	542.925	469.9	314.325	132	1880.7875
8990800.09		09		791079150849	6	542.925	469.9	314.325	132	1880.7875
8990800.10		10		791079150856	6	542.925	469.9	314.325	132	1880.7875
8990800.11		11		791079150863	6	542.925	469.9	314.325	132	1880.7875
8990800.12		12		791079150870	6	542.925	469.9	314.325	132	1880.7875
8990800.13		13		791079150887	6	542.925	469.9	314.325	132	1880.7875
8990800.14		14		791079150894	6	542.925	469.9	314.325	132	1880.7875
8990800.15		15		791079150900	6	542.925	469.9	314.325	132	1880.7875

Creation date: July 07, 2025

MAKE EVERY STEP COUNT